

# CLASSIC RANGE

## SLOW ROTATING JOINTS

For use with a variety of fluids  
7 bar maximum  
50 r.p.m. maximum



### Models

Model No.	Thread size
04017400	R1/8
04017500	R1/4
04017600	R3/8



**Pressure:**  
6 bar (Dynamic Pressure)

**Temperature:**  
-20 to +60°C

**Materials:**  
Housing and cap – Polyamide  
Filter – Felt insert



### Models – Plastic/Nylon

Model No.	Thread size	Length C	Diameter B
0014500000000000	G1/8	41	16
0014600000000000	G1/4	51	21
0014700000000000	G3/8	60	25
0014800000000000	G1/2	72	30

## FAST ROTATING JOINTS

Pressure and vacuum models  
For use with a variety of fluids  
7 bar maximum  
2000 r.p.m. maximum



### Models

Model No.	Medium	Thread size
04016100	Pressure	R1/4
04016200	Vacuum	R1/4

## HERION Silencer

Plastic/Nylon and Sintered Metal Series

**Pressure:**  
16 bar (Operating pressure)  
5 bar (Dynamic Pressure)

**Temperature:**  
-10 to +60°C

**Materials:**  
Housing – Sintered metal,  
Threaded base – Sintered metal



### Models – Sintered

Model No.	Thread size	Length C	Diameter B
0014510000000000	G1/8	28,5	8
0014610000000000	G1/4	34,5	12
0014710000000000	G3/8	36,5	15
0014810000000000	G1/2	45	19

## ENOTS 34 Series brass compression fittings

Spare parts



### Tubing nut

Model No.	O/D Tube
36050002	4
36050003	5
36050004	6
36050005	8
36050006	10
36050007	12
36050008	16

### Tubing sleeve

Model No.	O/D Tube
36050102	4
36050103	5
36050104	6
36050105	8
36050106	10
36050107	12
36050108	16